

美标汽车线

AMERICAN STANDARD AUTOMOBILE WIRE

GPT

产品说明

- 额定温度：80°C
- 参考标准：SAE J 1128
- 导体使用绞合 20~8AWG 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 通过 SAE J 1128 5.6 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于汽车内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 80°C
- Standard: SAE J 1128
- Stranded ,tinned or bare copper conductor 20~8AWG
- PVC insulation , ROHS compliant.
- Passes SAE J 1128 5.6 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For vehicle internal wiring of appliance

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

| 规格 AWG | 导体 CONDUCTOR | | | 绝缘 INSULATION | | 耐压强度 DIELECTRIC STRENGTH (VAC,1min) |
|-----------|---|----------------------------------|--------------------|-------------------------|--------------------|---|
| | 面积 CROSS SECTION (mm ²) | 构造 CONSTRUCTION (No. / mm) | 外径 DIA. (mm) | 厚度 THICKNESS (mm) | 外径 O.D. (mm) | |
| 20 | 0.50 | 7/0.31 | 0.93 | 0.59 | 2.10 | 1000 |
| 18 | 0.80 | 16/0.254 | 1.17 | 0.62 | 2.40 | 1000 |
| 16 | 1 | 26/0.254 | 1.49 | 0.61 | 2.70 | 1000 |
| 14 | 2 | 19/0.36 | 1.80 | 0.60 | 3.00 | 1000 |
| 12 | 3 | 19/0.45 | 2.25 | 0.68 | 3.60 | 1000 |
| 10 | 5 | 19/0.57 | 2.85 | 0.88 | 4.60 | 1000 |
| 8 | 8 | 19/0.71 | 3.55 | 1.08 | 5.70 | 1000 |

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval