

美标汽车线

AMERICAN STANDARD AUTOMOBILE WIRE

HDT

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品说明

- 额定温度：80℃
- 参考标准：SAE J 1128
- 导体使用绞合 20~8AWG 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 通过 SAE J 1128 5.6 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于汽车内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 80°C
- Standard: SAE J 1128
- Stranded, tinned or bare copper conductor 20~8AWG
- PVC insulation, RoHS compliant.
- Passes SAE J 1128 5.6 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For vehicle internal wiring of appliance

产品结构

CABLE CONSTRUCTION

规格 AWG	导体 CONDUCTOR			绝缘 INSULATION		耐压强度 DIELECTRIC STRENGTH (VAC,1min)
	面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	
20	0.50	7/0.31	0.93	0.94	2.80	1000
18	0.80	16/0.254	1.17	0.97	3.10	1000
16	1	26/0.254	1.49	1.06	3.60	1000
14	2	19/0.36	1.80	1.10	4.00	1000
12	3	19/0.45	2.25	1.28	4.80	1000
10	5	19/0.57	2.85	1.28	5.40	1000
8	8	19/0.71	3.55	1.53	6.60	1000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval