

电器配线

APPLIANCE WIRE

UL 1365 HOOK-UP WIRE

产品说明

- 额定温度：60℃
- 额定电压：300V
- 参考标准：UL758,UL1581
- 导体使用单支或绞合 30~16AWG 镀锡或裸铜
- PE 绝缘 ,PVC 护套，符合 RoHS 环保标准
- 通过 UL VW-1&CSA FT1 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 60℃
- Rated voltage: 300V
- Standard: UL758,UL1581
- Solid or stranded ,tinned or bare copper conductor 30~16AWG
- PE insulation , PVC jacket, RoHS compliant.
- Passes UL VW-1&CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

规格 AWG	导体 CONDUCTOR		绝缘 INSULATION		护套 JACKET		最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,1min)
	构造 CONSTRUCTION (No. / mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
30	7/0.10	0.30	0.58	1.55	0.38	2.40	381	2000
28	7/0.127	0.38	0.58	1.60	0.38	2.50	239	2000
26	7/0.16	0.48	0.58	1.70	0.38	2.60	150	2000
24	11/0.16	0.61	0.58	1.85	0.38	2.70	94.2	2000
22	17/0.16	0.76	0.58	2.00	0.38	2.90	59.4	2000
20	26/0.16	0.94	0.58	2.20	0.38	3.10	36.7	2000
18	16/0.254	1.17	0.58	2.45	0.38	3.30	23.2	2000
16	26/0.254	1.50	0.58	2.80	0.38	3.70	14.6	2000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval