

国标汽车线

CHINESE STANDARD AUTOMOBILE WIRE

QVR/QVR-105

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品说明

- 额定温度：70℃ 105℃
- 参考标准：JB/T 8139
- 导体使用绞合镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 通过 JB/T 8139 6.5.8 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于汽车内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 70℃ 105℃
- Standard: JB/T 8139
- Stranded, tinned or bare copper conductor
- PVC insulation, RoHS compliant.
- Passes JB/T 8139 6.5.8 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For vehicle internal wiring of appliance

产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE (Ω/km, 20℃, DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 1min)
面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No. / mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.2	12/0.15	0.60	0.33	1.25	95.0	1000
0.3	16/0.15	0.69	0.33	1.35	71.2	1000
0.4	23/0.15	0.83	0.34	1.50	49.6	1000
0.5	16/0.20	0.92	0.64	2.20	40.1	1000
0.75	24/0.20	1.13	0.69	2.50	26.7	1000
1.0	32/0.20	1.31	0.65	2.60	20.0	1000
1.5	30/0.25	1.58	0.64	2.85	13.7	1000
2.5	49/0.25	2.02	0.74	3.50	8.21	1000
4	56/0.30	2.59	0.91	4.40	5.09	1000
6	84/0.30	3.17	0.87	4.90	3.39	1000
10	84/0.40	4.23	1.04	6.30	1.95	1000
16	126/0.40	5.58	1.04	7.75	1.24	1000
25	196/0.40	6.96	1.35	9.80	0.795	1000
35	276/0.40	8.73	1.35	11.60	0.565	1000
50	396/0.40	10.20	1.55	13.40	0.393	1000
70	360/0.50	12.00	1.55	15.30	0.277	1000
95	475/0.50	13.00	1.65	16.60	0.210	1000
120	608/0.50	14.80	1.65	18.50	0.164	1000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval