

电机引出线

ELECTRIC MOTOR HOOK-UP WIRE

JYJ125 JYJ150 750V

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品说明

- 额定温度：125℃,150℃
- 额定电压：750V
- 参考标准：Q/320205 KADK01-2014
- 导体使用绞合 0.5~95mm² 镀锡或裸铜
- XLPE 绝缘,符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于 B 级、F 级、H 级电机绕组引接线

PRODUCT DESCRIPTION

- Rated temperature: 125℃,150℃
- Rated voltage: 750V
- Standard: Q/320205KADK01—2014
- Stranded ,tinned or bare copper conductor 0.5~95mm²
- XLPE insulation , RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For lead wiring of B、F、H insulation class motor

产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,1min)
规格 mm ²	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.50	16/0.20	0.92	0.60	2.25	40.1	3000
0.75	24/0.20	1.13	0.60	2.40	26.7	3000
1.0	32/0.20	1.31	0.60	2.60	20.0	3000
1.5	30/0.25	1.58	0.70	3.05	13.7	3000
2.5	49/0.25	2.02	0.70	3.60	8.21	3000
4.0	56/0.30	2.60	0.70	4.10	5.09	3000
6.0	84/0.30	3.42	0.80	5.20	3.39	3000
10	84/0.40	4.56	0.90	6.30	1.95	3000
16	126/0.40	5.60	1.00	8.00	1.24	3000
25	196/0.40	6.95	1.00	9.20	0.795	3000
35	276/0.40	8.74	1.00	10.90	0.565	3000
50	396/0.40	10.46	1.20	13.20	0.393	3000
70	360/0.50	12.50	1.20	15.20	0.277	3000
95	475/0.50	13.73	1.40	17.00	0.210	3000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval