

# 欧标电源线

## EUROPEAN STANDARD POWER CABLE

### H07V-U

### 产品结构图

### CABLE CONSTRUCTION DIAGRAM



### 产品说明

- 额定温度：70℃
- 额定电压：450/750V
- 参考标准：DIN VDE0281-3
- 导体使用单根 1.5~10mm<sup>2</sup> 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

### PRODUCT DESCRIPTION

- Rated temperature: 70℃
- Rated voltage: 450/750V
- Standard: DIN VDE0281-3
- Solid ,tinned or bare copper conductor 1.5~10mm<sup>2</sup>
- PVC insulation , RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

### 产品结构

### CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,5min)
面积 CROSS SECTION (mm <sup>2</sup> )	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
1.5	1/1.38	1.38	0.70	2.90	13.3	2500
2.5	1/1.78	1.78	0.80	3.50	7.98	2500
4	1/2.25	2.25	0.80	3.95	4.95	2500
6	1/2.76	2.76	0.80	4.45	3.30	2500
10	1/3.58	3.58	1.00	5.80	1.91	2500

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval