

## 欧标电源线

### EUROPEAN STANDARD POWER CABLE

## H07V-K

### 产品结构图

#### CABLE CONSTRUCTION DIAGRAM



### 产品说明

- 额定温度：70℃
- 额定电压：450/750V
- 参考标准：DIN VDE0281-3
- 导体使用绞合 1.5~120mm<sup>2</sup> 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

### 产品结构

#### CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km, 20°C, DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 5min)
面积 CROSS SECTION (mm <sup>2</sup> )	构造 CONSTRUCTION (No. / mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
1.5	30/0.25	1.58	0.70	3.10	13.3	2500
2.5	49/0.25	2.02	0.80	3.75	7.98	2500
4	56/0.30	2.60	0.80	4.30	4.95	2500
6	84/0.30	3.42	0.80	5.20	3.30	2500
10	84/0.40	4.56	1.00	6.70	1.91	2500
16	126/0.40	5.60	1.00	7.80	1.21	2500
25	196/0.40	6.95	1.20	9.60	0.795	2500
35	276/0.40	8.74	1.20	11.30	0.554	2500
50	396/0.40	10.46	1.40	13.60	0.386	2500
70	360/0.50	12.50	1.40	15.60	0.272	2500
95	475/0.50	13.73	1.60	17.30	0.206	2500
120	608/0.50	15.50	1.60	19.10	0.161	2500

### PRODUCT DESCRIPTION

- Rated temperature: 70°C
- Rated voltage: 450/750V
- Standard: DIN VDE0281-3
- Stranded, tinned or bare copper conductor 1.5~120mm<sup>2</sup>
- PVC insulation, RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval