

## 德标汽车线

## GERMAN STANDARD AUTOMOBILE WIRE

# FLRYK-B

### 产品说明

- 额定温度：80℃
- 参考标准：DIN72551/1991
- 导体使用绞合 0.35~6.0mm<sup>2</sup> 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 通过 DIN 72551-5/1991 3.7.1 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于汽车内部连接线

### PRODUCT DESCRIPTION

- Rated temperature: 80℃
- Standard: DIN72551/1991
- Stranded, tinned or bare copper conductor 0.35~6.0mm<sup>2</sup>
- PVC insulation, RoHS compliant.
- Passes DIN 72551-5/1991 3.7.1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For vehicle internal wiring of appliance

### 产品结构图

### CABLE CONSTRUCTION DIAGRAM



### 产品结构

### CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km, 20℃, DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 30min)
面积 CROSS SECTION (mm <sup>2</sup> )	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.35	12/0.20	0.80	0.25	1.30	54.5	1000
0.5	16/0.20	0.92	0.29	1.50	38.2	1000
0.75	24/0.20	1.13	0.34	1.80	25.4	1000
1.0	32/0.20	1.31	0.35	2.00	19.1	1000
1.5	30/0.25	1.58	0.36	2.30	13.0	1000
2.5	50/0.25	2.04	0.43	2.90	7.8	1000
4.0	56/0.30	2.59	0.51	3.60	4.8	1000
6.0	84/0.30	3.17	0.52	4.20	3.2	1000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval