

# 德标汽车线

## GERMAN STANDARD AUTOMOBILE WIRE

### FLRYW-A

### 产品结构图

### CABLE CONSTRUCTION DIAGRAM



### 产品说明

- 额定温度：100℃
- 参考标准：DIN72551/1991
- 导体使用绞合 0.22~2.5mm<sup>2</sup> 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 通过 DIN 72551-5/1991 3.7.1 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于汽车内部连接线

### PRODUCT DESCRIPTION

- Rated temperature: 100℃
- Standard: DIN72551/1991
- Stranded ,tinned or bare copper conductor 0.22~2.5mm<sup>2</sup>
- PVC insulation , RoHS compliant.
- Passes DIN 72551-5/1991 3.7.1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For vehicle internal wiring of appliance

### 产品结构

### CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,30min)
面积 CROSS SECTION (mm <sup>2</sup> )	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.22	7/0.21	0.63	0.26	1.15	86.5	1000
0.35	7/0.26	0.78	0.24	1.25	54.5	1000
0.5	19/0.19	0.95	0.28	1.50	38.2	1000
0.75	19/0.23	1.15	0.33	1.80	25.4	1000
1.0	19/0.26	1.30	0.35	2.00	19.1	1000
1.5	19/0.32	1.60	0.35	2.30	13.0	1000
2.5	19/0.41	2.05	0.43	2.90	7.8	1000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval