

电器配线

APPLIANCE WIRE

聚氯乙烯绝缘线缆 PVC INSULATION WIRE

UL 1235 HOOK-UP WIRE

产品说明

- 额定温度：105℃
- 额定电压：600V
- 参考标准：UL758,U1581
- 导体使用单支或绞合 18~8AWG 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 通过 UL VW-1&CSA FT1 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 105℃
- Rated voltage: 600V
- Standard: UL758,UL1581
- Solid or stranded ,tinned or bare copper conductor 18~8AWG
- PVC insulation , RoHS compliant.
- Passes UL VW-1&CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance.

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR		绝缘 INSULATION			最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,1min)
规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
18	16/0.254	1.15	1.52	4.35	23.2	2000
16	26/0.254	1.50	1.52	4.70	14.6	2000
14	41/0.254	1.88	1.52	5.05	8.96	2000
12	65/0.254	2.36	1.52	5.55	5.64	2000
10	105/0.254	3.10	1.52	6.30	3.546	2000
8	168/0.254	4.25	1.52	7.50	2.23	2000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval