

电器配线

APPLIANCE WIRE

多芯聚氯乙烯护套线缆 MULTIPLE PVC INSULATED CABLE

UL 2464 COMPUTER CABLE

产品说明

- 额定温度：80℃
- 额定电压：300V
- 参考标准：UL758,UL1581
- 导体使用单支或绞合镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- PVC 护套,符合 RoHS 环保标准
- 镀锡或裸铜编织屏蔽
- 通过 UL VW-1、CSA FT1 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于电脑连接线

PRODUCT DESCRIPTION

- Rated temperature: 80℃
- Rated voltage: 300V
- Standard: UL758,UL1581
- Solid or stranded ,tinned or bare copper conductor
- PVC insulation , RoHS compliant.
- PVC jacket , RoHS compliant.
- Tinned or bare copper wire braid shield
- Passes UL VW-1、CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For computer wiring of appliance

导体 CONDUCTOR			绝缘 INSULATION		屏蔽 SHIELD	排流线 DRAIN	编织 BRAID	护套 JACKET		最大导体电阻 MAX. COND. RESISTANCE (Ω/km,20°C,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,1min)	
规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	芯数 (No.)	厚度 THICKNESS (mm)	外径 O.D. (mm)	构造 CONSTRUCTION (No./mm)	构造 CONSTRUCTION (No./mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)			
26	7/0.16	0.48	2	0.38	1.30	Al-mylar		16/5/0.10	0.80	4.70	150	2000
			3	0.38	1.30	Al-mylar		16/6/0.10	0.80	4.90		2000
			4	0.38	1.30	Al-mylar		16/7/0.10	0.78	5.20		2000
			5	0.38	1.30	Al-mylar	7/0.16	16/7/0.10	0.79	5.60		2000
			6	0.38	1.30	Al-mylar		16/8/0.10	0.80	6.00		2000
			7	0.38	1.30	Al-mylar		16/8/0.10	0.80	6.00		2000
			8	0.38	1.30	Al-mylar		24/6/0.10	0.81	6.40		2000
			9	0.38	1.30	Al-mylar		24/7/0.10	0.85	7.00		2000
			10	0.38	1.30	Al-mylar		24/7/0.10	0.85	7.40		2000
			24	11/0.16	0.61	2	0.38	1.40	Al-mylar			16/6/0.10
3	0.38	1.40				Al-mylar		16/6/0.10	0.79	5.10	2000	
4	0.38	1.40				Al-mylar		16/7/0.10	0.81	5.50	2000	
5	0.38	1.40				Al-mylar	11/0.16	16/8/0.10	0.81	5.90	2000	
6	0.38	1.40				Al-mylar		24/6/0.10	0.80	6.30	2000	
7	0.38	1.40				Al-mylar		24/6/0.10	0.80	6.30	2000	
8	0.38	1.40				Al-mylar		24/6/0.10	0.79	6.70	2000	
9	0.38	1.40				Al-mylar		24/7/0.10	0.86	7.40	2000	
10	0.38	1.40				Al-mylar		24/8/0.10	0.85	7.80	2000	
22	17/0.16	0.76				2	0.38	1.60	Al-mylar		16/7/0.10	0.80
			3	0.38	1.60	Al-mylar		16/7/0.10	0.83	5.60	2000	
			4	0.38	1.60	Al-mylar		16/8/0.10	0.82	6.00	2000	
			5	0.38	1.60	Al-mylar	7/0.16	24/6/0.10	0.84	6.50	2000	
			6	0.38	1.60	Al-mylar		24/7/0.10	0.80	6.90	2000	
			7	0.38	1.60	Al-mylar		24/7/0.10	0.80	6.90	2000	
			8	0.38	1.60	Al-mylar		24/7/0.10	0.86	7.50	2000	
			9	0.38	1.60	Al-mylar		24/8/0.10	0.84	8.10	2000	
			10	0.38	1.60	Al-mylar		24/8/0.10	0.85	8.60	2000	
			20	26/0.16	0.94	2	0.38	1.80	Al-mylar		16/8/0.10	0.80
3	0.38	1.80				Al-mylar		16/8/0.10	0.81	6.00	2000	
4	0.38	1.80				Al-mylar		24/6/0.10	0.83	6.50	2000	
5	0.38	1.80				Al-mylar	26/0.16	24/6/0.10	0.87	7.10	2000	
6	0.38	1.80				Al-mylar		24/7/0.10	0.85	7.60	2000	
7	0.38	1.80				Al-mylar		24/7/0.10	0.85	7.60	2000	
8	0.38	1.80				Al-mylar		24/8/0.10	0.88	8.20	2000	
9	0.38	1.80				Al-mylar		24/8/0.12	0.88	9.00	2000	
10	0.38	1.80				Al-mylar		24/8/0.12	0.86	9.50	2000	

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval