

电器配线

APPLIANCE WIRE

UL 3385 HOOK-UP WIRE

产品说明

- 额定温度：105℃
- 额定电压：300V
- 参考标准：UL758,UL1581
- 导体使用单支或绞合 30~10AWG 镀锡或裸铜
- XLPE 绝缘,符合 RoHS 环保标准
- 通过 CSA FT2 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 105℃
- Rated voltage: 300V
- Standard: UL758,UL1581
- Solid or stranded ,tinned or bare copper conductor 30~10AWG
- XLPE insulation , RoHS compliant.
- Passes CSA FT2 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,1min)
规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
30	7/0.10	0.30	0.38	1.15	381	2000
28	7/0.127	0.38	0.38	1.20	239	2000
26	7/0.16	0.48	0.38	1.30	150	2000
24	11/0.16	0.61	0.38	1.45	94.2	2000
22	17/0.16	0.76	0.38	1.60	59.4	2000
20	26/0.16	0.94	0.38	1.80	36.7	2000
18	16/0.254	1.15	0.38	2.00	23.2	2000
16	26/0.254	1.50	0.38	2.40	14.6	2000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval