

欧标电源线

EUROPEAN STANDARD POWER CABLE

H07Z-U

产品说明

- 额定温度：90℃
- 额定电压：450/750V
- 参考标准：DIN VDE0282-9
- 导体使用单根 1.5~10mm² 镀锡或裸铜
- 低烟无卤聚烯烃绝缘，符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 90℃
- Rated voltage: 450/750V
- Standard: DIN VDE0282-9
- Solid ,tinned or bare copper conductor 1.5~10mm²
- LSZH insulation , RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,5min)
面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No. / mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
1.5	1/1.38	1.38	0.70	2.90	13.3	2500
2.5	1/1.78	1.78	0.80	3.50	7.98	2500
4	1/2.25	2.25	0.80	3.95	4.95	2500
6	1/2.76	2.76	0.80	4.45	3.30	2500
10	1/3.58	3.58	1.00	5.80	1.91	2500

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval