

欧标电源线

EUROPEAN STANDARD POWER CABLE

H07V-R

产品说明

- 额定温度：70℃
- 额定电压：450/750V
- 参考标准：DIN VDE0281-3
- 导体使用绞合 1.5~120mm² 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 70℃
- Rated voltage: 450/750V
- Standard: DIN VDE0281-3
- Stranded ,tinned or bare copper conductor 1.5~120mm²
- PVC insulation , RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

| 导体 CONDUCTOR | | | 绝缘 INSULATION | | 最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC) | 耐压强度 DIELECTRIC STRENGTH (VAC,5min) |
|--|--------------------------------|--------------------|-------------------------|--------------------|---|---|
| 面积 CROSS SECTION (mm ²) | 构造 CONSTRUCTION (No./mm) | 外径 DIA. (mm) | 厚度 THICKNESS (mm) | 外径 O.D. (mm) | | |
| 1.5 | 7/0.52 | 1.56 | 0.70 | 3.05 | 13.3 | 2500 |
| 2.5 | 7/0.68 | 2.04 | 0.80 | 3.75 | 7.98 | 2500 |
| 4 | 7/0.85 | 2.55 | 0.80 | 4.25 | 4.95 | 2500 |
| 6 | 7/1.04 | 3.12 | 0.80 | 4.80 | 3.30 | 2500 |
| 10 | 7/1.35 | 4.05 | 1.00 | 6.20 | 1.91 | 2500 |
| 16 | 7/1.70 | 5.10 | 1.00 | 7.30 | 1.21 | 2500 |
| 25 | 7/2.14 | 6.42 | 1.20 | 9.00 | 0.795 | 2500 |
| 35 | 7/2.52 | 7.56 | 1.20 | 10.15 | 0.554 | 2500 |
| 50 | 19/1.78 | 9.90 | 1.40 | 13.00 | 0.386 | 2500 |
| 70 | 19/2.14 | 10.70 | 1.40 | 13.70 | 0.272 | 2500 |
| 95 | 19/2.52 | 12.60 | 1.60 | 16.10 | 0.206 | 2500 |

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval