

欧标电源线

EUROPEAN STANDARD POWER CABLE

H05V2-R

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品说明

- 额定温度：90℃
- 额定电压：300/500V
- 参考标准：DIN VDE0281-7
- 导体使用绞合 0.5~1mm² 镀锡或裸铜
- PVC 绝缘,符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 90℃
- Rated voltage: 300/500V
- Standard: DIN VDE0281-7
- Stranded, tinned or bare copper conductor 0.5~1mm²
- PVC insulation, RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km, 20°C, DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 5min)
面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.5	7/0.30	0.90	0.60	2.20	40.1	2000
0.75	7/0.37	1.11	0.60	2.40	26.0	2000
1	7/0.43	1.29	0.60	2.60	19.5	2000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval