

欧标电源线

EUROPEAN STANDARD POWER CABLE

H05Z-U

产品说明

- 额定温度：90℃
- 额定电压：300/500V
- 参考标准：DIN VDE0282-9
- 导体使用单根 0.5~1mm² 镀锡或裸铜
- 低烟无卤聚烯缘绝缘，符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 90℃
- Rated voltage: 300/500V
- Standard: DIN VDE0282-9
- Solid ,tinned or bare copper conductor 0.5~1mm²
- LSZH insulation , RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20℃,DC)	耐压强度 DIELECTRIC STRENGTH (VAC,5min)
面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No. / mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.5	1/0.80	0.80	0.60	2.10	40.1	2000
0.75	1/0.97	0.97	0.60	2.40	26.0	2000
1	1/1.17	1.17	0.60	2.50	19.5	2000

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval