

欧标电源线

EUROPEAN STANDARD POWER CABLE

H07Z-R

产品结构图

CABLE CONSTRUCTION DIAGRAM



产品说明

- 额定温度：90℃
- 额定电压：450/750V
- 参考标准：DIN VDE0282-9
- 导体使用绞合 1.5~120mm² 镀锡或裸铜
- 低烟无卤聚烯烃绝缘，符合 RoHS 环保标准
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 90℃
- Rated voltage: 450/750V
- Standard: DIN VDE0282-9
- Stranded, tinned or bare copper conductor 1.5~120mm²
- LSZH insulation, RoHS compliant.
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance

产品结构

CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km, 20°C, DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 5min)
面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No. / mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
1.5	7/0.52	1.56	0.70	3.05	13.3	2500
2.5	7/0.68	2.04	0.80	3.75	7.98	2500
4	7/0.85	2.55	0.80	4.25	4.95	2500
6	7/1.04	3.12	0.80	4.80	3.30	2500
10	7/1.35	4.05	1.00	6.20	1.91	2500
16	7/1.70	5.10	1.00	7.30	1.21	2500
25	7/2.14	6.42	1.20	9.00	0.795	2500
35	7/2.52	7.56	1.20	10.15	0.554	2500
50	19/1.78	9.90	1.40	13.00	0.386	2500
70	19/2.14	10.70	1.40	13.70	0.272	2500
95	19/2.52	12.60	1.60	16.10	0.206	2500

备注：详细尺寸以产品规格书为准

NOTE: The product's detailed description please refer to the specification for approval